

Product Name **COLOURpyne® Particleboard LPM MR**

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier Name **CARTER HOLT HARVEY WOODPRODUCTS AUSTRALIAN GROUP OF COMPANIES**

Address Level 6, Tower A, Zenith Centre, 821 Pacific Hwy, Chatswood, NSW, AUSTRALIA, 2067

Telephone 1300 658 828

Fax 1800 891 881

Emergency 1300 658 828

Email marketing@chhwoodproducts.com.au

Synonym(s) COLOURpyne® Moisture Resistant PYNEboard® • COLOURpyne® MR PYNEboard® • COLOURpyne® E1 Moisture Resistant PYNEboard® • COLOURpyne® E1 MR PYNEboard® • COLOURpyne® E0 Moisture Resistant PYNEboard® • COLOURpyne® E0 MR PYNEboard® • COLOURpyne® PYNEboard® MR • PYNEboard® White Moisture Resistant • PYNEboard® White MR • PYNEboard® White Moisture Resistant Particleboard • PYNEboard® White MR Particleboard • PYNEboard® White E1 Moisture Resistant • PYNEboard® White E1 MR • PYNEboard® White E1 Moisture Resistant Particleboard • PYNEboard® White E1 MR Particleboard • PYNEboard® White E0 Moisture Resistant • PYNEboard® White E0 MR • PYNEboard® White Moisture Resistant Particleboard • PYNEboard® White E0 MR Particleboard • PYNEpanel Moisture Resistant • PYNEpanel MR • PYNEpanel Thick Edge Moisture Resistant • PYNEpanel Thick Edge MR •

Use(s) BUILDING BOARD • CABINETS • DOOR FACINGS • FURNITURE

SDS Date 26 May 2011

2. HAZARDS IDENTIFICATION

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

UN No. None Allocated **DG Class** None Allocated **Subsidiary Risk(s)** None Allocated

Packing Group None Allocated **Hazchem Code** None Allocated **EPG** None Allocated

3. COMPOSITION/ INFORMATION ON INGREDIENTS

Ingredient	Formula	CAS No.	Content
PARAFFIN WAX	Not Available	8002-74-2	<2%
WOOD(S) (SOFTWOOD/HARDWOOD)	Not Available	Not Available	>70%
MELAMINE/UREA/FORMALDEHYDE RESIN	Not Available	25036-13-9	<15%
MOISTURE	H ₂ O	Not Available	5-13%
PAPER	Not Available	Not Available	<2%
MELAMINE FORMALDEHYDE RESIN	Not Available	9003-08-1	<1%
UREA-FORMALDEHYDE RESIN	Not Available	9011-05-6	<1%
DYE	Not Available	Not Available	<0.1%

4. FIRST AID MEASURES

Eye	If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
Inhalation	If inhaled, remove from contaminated area. Apply artificial respiration if not breathing.
Skin	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre or a doctor.
Ingestion	For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). Due to product form and application, ingestion is considered unlikely.
Advice to Doctor	Treat symptomatically

5. FIRE FIGHTING MEASURES

Flammability	Combustible. May evolve toxic gases (carbon/ nitrogen oxides, ammonia, formaldehyde, hydrocarbons) when heated to decomposition. May also evolve hydrogen cyanide when heated to decomposition.
Fire and Explosion	Dry wood dust in high concentrations-in-air and at the temperatures > 204°C (>40g of dust per m3 of air) may spontaneously explode. Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.
Extinguishing	Dry agent, carbon dioxide, foam or water fog. Prevent contamination of drains or waterways.
Hazchem Code	None Allocated

6. ACCIDENTAL RELEASE MEASURES

Spillage	If spilt, collect and reuse where possible.
-----------------	---

7. STORAGE AND HANDLING

Storage	Store in a cool, dry area. Also store removed from oxidising agents and acids.
Handling	Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

Exposure Stds	Ingredient	Reference	TWA		STEL	
			ppm	mg/m3	ppm	mg/m3
	Paraffin wax (fume)	SWA (AUS)	--	2	--	--
	Wood dust (soft wood)	SWA (AUS)	--	5	--	10
	Formaldehyde	SWA (AUS)	1	1.2	2	2.5

Biological Limits	No biological limit allocated.
Engineering Controls	Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended. Maintain dust levels below the recommended exposure standard.
PPE	Wear leather gloves. Where dust is generated, wear dust-proof goggles, cotton/PVC gloves, a Class P1 (Particulate) respirator, coveralls or protective clothing. Work areas should be cleaned at least twice daily by vaccum or wet methods. If cutting or sanding with potential for dust generation, wear: dust-proof goggles and a Class P1 (Particulate) respirator.



9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	PRESSED BOARDS	Solubility (Water)	INSOLUBLE
Odour	SLIGHT ODOUR	Specific Gravity	NOT AVAILABLE
pH	NOT AVAILABLE	% Volatiles	NOT AVAILABLE
Vapour Pressure	NOT AVAILABLE	Flammability	COMBUSTIBLE
Vapour Density	NOT AVAILABLE	Flash Point	NOT AVAILABLE
Boiling Point	NOT AVAILABLE	Upper Explosion Limit	NOT AVAILABLE
Melting Point	NOT AVAILABLE	Lower Explosion Limit	NOT AVAILABLE
Evaporation Rate	NOT AVAILABLE		
Autoignition Temperature	> 200°C	Density	500 kg/m3 to 800 kg/m3

10. STABILITY AND REACTIVITY

Chemical Stability	Stable under recommended conditions of storage.
Conditions to Avoid	Avoid heat, sparks, open flames and other ignition sources.
Material to Avoid	Incompatible with oxidising agents (eg. nitrates) and acids (eg. hydrochloric acid).
Hazardous Decomposition Products	May evolve toxic gases (carbon/ nitrogen oxides, ammonia, formaldehyde, hydrocarbons) when heated to decomposition. May also evolve hydrogen cyanide when heated to decomposition.
Hazardous Reactions	Polymerization is not expected to occur.

11. TOXICOLOGICAL INFORMATION

Health Hazard Summary	Low to moderate toxicity. Use safe work practices to avoid eye or skin contact and inhalation. This product is bonded by formaldehyde resin and formaldehyde may be released during machining. Product may also release small quantities (<0.01%) of formaldehyde in gaseous form that may dissipate over time. Adverse health effects associated with over exposure formaldehyde are not anticipated due to the product form and its low concentration. Formaldehyde is a respiratory and skin sensitiser, and is classified as a confirmed human carcinogen (IARC Group 1). Wood dust is also classified as a confirmed human carcinogen (IARC Group 1).
Eye	Due to product form and nature of use, the potential for exposure is reduced. Product may only present a hazard if dust is generated. Contact may result in mechanical irritation.
Inhalation	Exposure considered unlikely. An inhalation hazard is not anticipated unless cut, drilled or sanded with dust generation, which may result in irritation of the nose and throat. If heated, over exposure to fumes may result in irritation of the nose and throat, with nausea and headache. Formaldehyde is classified as a confirmed human carcinogen (IARC Group 1) and respiratory sensitiser. Repeated chronic exposure to uncontrolled wood dust increases the risk of nasal cavity cancer and lung fibrosis (scarring).
Skin	Low irritant. Prolonged or repeated exposure to dust may result in mild irritation. May cause sensitisation by skin contact.
Ingestion	Ingestion is considered unlikely due to product form. Abdominal discomfort may be experienced if dust is ingested.
Toxicity Data	PARAFFIN WAX (8002-74-2) TDLo (Subcutaneous): 120 mg/kg (rat) MELAMINE FORMALDEHYDE RESIN (9003-08-1) Carcinogenicity: Not classifiable as to its carcinogenicity (IARC Group 3) LD50 (Ingestion): 3161 mg/kg (rat)

12. ECOLOGICAL INFORMATION

Environment	Limited ecotoxicity data was available for this product at the time this report was prepared. Ensure appropriate measures are taken to prevent this product from entering the environment.
--------------------	--

13. DISPOSAL CONSIDERATIONS

Waste Disposal	Reuse where possible. Not regulated as a hazardous waste by Australian environmental authorities. Off-cuts and general waste material should be placed in containers and disposed of at approved landfill sites or burnt in an approved furnace or incinerator in accordance with disposal authority guidelines. Do not burn in barbeques, combustion stoves or open fires in the home as irritating gases may be evolved.
Legislation	Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

Shipping Name	None Allocated				
UN No.	None Allocated	DG Class	None Allocated	Subsidiary Risk(s)	None Allocated
Packing Group	None Allocated	Hazchem Code	None Allocated	EPG	None Allocated

15. REGULATORY INFORMATION

Poison Schedule A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).

AICS All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Additional Information The dust generated from this product is hazardous according to the criteria of Safe Work Australia.

Early fire hazard properties when tested to AS/NZS 1530 Part 3:

Ignitability index: 14 - 16

Spread of flame index: 7 - 8

Heat evolved index: 6 - 10

Smoke developed index: 3 - 4

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

COMBUSTIBLE - EXPLOSIVE CARBONACEOUS DUST: Carbonaceous/organic dusts have the potential, with dispersion, to present an explosion hazard if an ignition source exists. All equipment used to handle, transfer or store this product **MUST BE** cleaned thoroughly prior to cutting, welding, drilling or exposure to any other form of heat or ignition sources. If bulk stored, containers should be ventilated on a routine basis to avoid vapour accumulation (where applicable, eg for flocculants).

ABBREVIATIONS:

ADB - Air-Dry Basis.

BEI - Biological Exposure Indice(s)

CAS# - Chemical Abstract Service number - used to uniquely identify chemical compounds.

CNS - Central Nervous System.

EINECS - European INventory of Existing Commercial chemical Substances.

IARC - International Agency for Research on Cancer.

M - moles per litre, a unit of concentration.

mg/m³ - Milligrams per cubic metre.

NOS - Not Otherwise Specified.

NTP - National Toxicology Program.

OSHA - Occupational Safety and Health Administration.

pH - relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).

ppm - Parts Per Million.

RTECS - Registry of Toxic Effects of Chemical Substances.

SWA - Safe Work Australia

TWA/ES - Time Weighted Average or Exposure Standard.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a Chem Alert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this Chem Alert report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

Report Status This document has been compiled by RMT on behalf of the manufacturer of the product and serves as the manufacturer's Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate

Product Name **COLOURpyne® Particleboard LPM MR**

safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared By Risk Management Technologies
5 Ventnor Ave, West Perth
Western Australia 6005
Phone: +61 8 9322 1711
Fax: +61 8 9322 1794
Email: info@rmt.com.au
Web: www.rmt.com.au

SDS Date: 26 May 2011

End of Report